

Technical data sheet

Industrial vertical cable ladder, 6 m W40

Item number: 6013864



Vertical ladder of side height 80 mm with screwed-in rungs.
The vertical ladder is shipped in an unmounted state.
The appropriate U clamp is type 2056W.



St

Steel

FT

Hot-dip galvanised

Master data

Item number	6013864
Description 1	Vertical ladder industrial
Description 2	with W 40 rung
Manufacturer	OBO
Dimension	600x6000
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	6
Unit of quantity	Metre
Weight	1454 kg
Weight unit	kg/100 m

Technical data sheet

Industrial vertical cable ladder, 6 m W40

Item number: 6013864



Dimensions

The drawing shows a side view of the cable ladder with a total length of 6000 mm. It consists of three sections: two side sections of 300 mm each and a central section of 600 mm. The rungs are spaced at 600 mm intervals. The width of the ladder is 600 mm. The height of the rungs is 80 mm. The side wall version is shown with a 40 mm offset. A detail view shows the rung profile with a width of 42 mm and a height of 80 mm.

Length	6,000 mm
Width	600 mm
Height	80 mm
Dimension B	600 mm

Technical data	
Side wall version	I profile
Version of the rungs	Profile unperforated
Maintain electrical functions	no
Rustproof steel, pickled	no
Side perforation	yes
Rung distance	600 mm